

KS H₂O

10 BE W	13 BE W	13 BE W
---------	---------	---------

Modello	Model	Modèle	Modell	Modelo		KS 10 BT E M W	KS 13 BT E M W	KS 13 BT E T W	
Campo applicazione	Application field	Champe d'application	Anwendungsbereich	Applicatiegebied	°C	-18 ÷ -22	-18 ÷ -22	-18 ÷ -22	
Alimentazione	Power supply	Alimentation	Netzanschluß	Stroomvoorziening		230V/1/50Hz	230V/1/50Hz	400V/3/50Hz	
Corrente max. assorbita	Max. absorbed current	Courant absorbé max.	Max. absorbierter Strom	Max. geabsorbeerde stroom	A	7,8	9,6	6,8	
Potenza max. assorbita	Max. absorbed power	Puissance max. absorbée	Max. aufgenommene Leistung	Max. opgenomen vermogen	kW	1,6	1,9	2,9	
Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Koelmiddel		R404A/R507/ R452A/R448A/ R449A	R404A/R507/ R452A/R448A/ R449A	R404A/R507/ R452A/R448A/ R449A	
CMP	Resa *	Capacity *	Puissance *	Leistung *	Prestatie *	W	734	884	835
	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Stroomafname	kW	1,65	2,05	2,05
	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Nominaal vermogen	CV	1,2	1,7	1,7
	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Compressortype		E	E	E
EVP	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Lamellenafstand	mm	6 ÷ 12	6 ÷ 12	6 ÷ 12
	Sbrinamento	Defrost	Dégivrage	Abtauung	Ontdooiing		EL	EL	EL
	Espansione	Expansion	Expansion	Expansion	Expansie		VT	VT	VT
	Ventilatori	Fan	Ventilateur	Ventilator	Ventilator		2 x Ø254	2 x Ø254	2 x Ø254
	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Nominale stroomafname	W	146	146	146
	Portata aria	Air volume	Debit d' air	Volumenstrom	Luchtvermogen	m³/h	1300	1300	1300
	Freccia d' aria	Air throw	Projection d'air	Reichweite	Reikwijdte	m	9	9	9
	Peso netto	Net Weight	Poids net	Nettogewicht	Nettogewicht	kg	67	68	68
Peso lordo	Gross weight	Poids brut	Bruttogewicht	Brutogewicht	kg	94	95	95	
Codice	Code	Code	Kodex	Kode		111103900	111103901	ks_R452_W_19	
* = Te: -30°C / Tcond: +40°C					Imballi	mm	1260		
					Packing	X			
					Emballage	mm	600		
					Y				
					Verpackung	mm	875		
					Z				
					Embalajes	mm	-		
					X				
					Y	mm	-		
					Z	mm	-		

C : Capillare / Capillary / Capillaire / Kapillar / Capillair
CMP : Compressore / Compressor / Compresseur / Kompressorleistung / Compressor
CND : Condensatore / Condenser / Condenseur / Verflüssiger / Condensor
E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermetische
EVP : Evaporatore / Evaporateur / Evaporateur / Verdampfer / Verdampfer
HG : Gas caldo / Hot gas / Gaz chaud / Heissgas / Heet gas
P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung
S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semi hermetisch

Ta : Temperatura ambiente / Ambient temperature / Température ambiante
Umgebungstemperatur / Omgevingstemperatuur
Tc : Temperatura cella / Cold room temperature / Température chambre froid
Kühlraumtemperatur / Koude kamertemperatuur
Te : Temperatura evaporazione / evaporation temperature / température d'évaporation
Verdampfungstemperatur / verdampingstemperatuur
Tcond : Temperatura condensazione / condensation temperature / température de condensation
Kondensationstemperatur / condensatietemperatuur
V : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Koelkamervolume
VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches
Expansionsventil / Expansieklep

