

KS H₂O

18 BE W
23 BS W
27 BE W

	Modello	Model	Modèle	Modell	Modelo		KS 18 BT E T W	KS 23 BT S T W	KS 27 BT E T W
	Campo applicazione	Application field	Champe d'application	Anwendungsbereich	Applicatiegebied	°C	-18 ÷ -22	-18 ÷ -22	-18 ÷ -22
	Alimentazione	Power supply	Alimentation	Netzanschluß	Stroomvoorziening		400V/3/50Hz	400V/3/50Hz	400V/3/50Hz
	Corrente max. assorbita	Max. absorbed current	Courant absorbé max.	Max. absorbierter Strom	Max. geabsorbeerde stroom	A	7,8	18,5	8,1
	Potenza max. assorbita	Max. absorbed power	Puissance max. absorbée	Max. aufgenommene Leistung	Max. opgenomen vermogen	kW	3,3	3,8	3,6
	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Koelmiddel		R404A/R507/ R452A/R448A/ R449A	R404A/R507/ R452A/R448A/ R449A	R404A/R507/ R452A/R448A/ R449A
CMP	Resa *	Capacity *	Puissance *	Leistung *	Prestatie *	W	1318	1788	1772
	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Stroomafname	kW	2,35	3,79	3,65
	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Nominaal vermogen	CV	1,8	1,5	2,4
	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Compressortype		E	S	E
EVP	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Lamellenafstand	mm	6 ÷ 12	6 ÷ 12	6 ÷ 12
	Sbrinamento	Defrost	Dégivrage	Abtauung	Ontdooiing		EL	EL	EL
	Espansione	Expansion	Expansion	Expansion	Expansie		VT	VT	VT
	Ventilatori	Fan	Ventilateur	Ventilator	Ventilator		3 x Ø254	3 x Ø254	3 x Ø254
	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Nominale stroomafname	W	219	219	219
	Portata aria	Air volume	Debit d' air	Volumenstrom	Luchtvermogen	m³/h	1950	1950	1950
	Freccia d' aria	Air throw	Projection d'air	Reichweite	Reikwijdte	m	11	11	11
	Peso netto	Net Weight	Poids net	Nettogewicht	Nettogewicht	kg	97	107	101
	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Brutogewicht	kg	130	140	134
	Codice	Code	Code	Kodex	Kode		111103999	111103910	111103909
* = Te: -30°C / Tcond: +40°C					Imballi	mm	1452		
					Packing	X			
					Emballage	mm	632		
					Verpackung	mm	906		
					Embalajes	mm			
					X		-		
					Y	mm	-		
					Z	mm	-		

C : Capillare / Capillary / Capillaire / Kapillar / Capillair
 CMP : Compressore / Compressor / Compresseur / Kompressorleistung / Compressor
 CND : Condensatore / Condenser / Condenseur / Verflüssiger / Condensor
 E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermetische
 EVP : Evaporatore / Evaporateur / Evaporateur / Verdampfer / Verdampfer
 HG : Gas caldo / Hot gas / Gaz chaud / Heissgas / Heet gas
 P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung
 Koelcapaciteit
 S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch /
 Semi hermetisch

Ta : Temperatura ambiente / Ambient temperature / Température ambiante
 Umgebungstemperatur / Omgevingstemperatuur
 Tc : Temperatura cella / Cold room temperature / Température chambre froid
 Kühlraumtemperatur / Koude kamertemperatuur
 Te : Temperatura evaporazione / evaporation temperature / température d'évaporation
 Verdampfungstemperatur / verdampingstemperatuur
 Tcond : Temperatura condensazione / condensation temperature / température de condensation
 Kondensationstemperatur / condensatietemperatuur
 V : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Koelkamervolume
 VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches
 Expansionsventil / Expansieklep

